

delpo

TSP LK32II

Mobile Label printer



Key features

- Support direct USB charging;
- Long lasting battery life;
- Dual mode bluetooth;
- OLED screen available;
- TSPL, EPL, ZPL, DPL, CPCL, ESC/POS command compatible.

Applications



Shopping



Mart



Restaurant



Hospital




Coffee Shop



Ticketing

TSP LK32II

Mobile Label Printer



Printing		TSP LK32II
Resolution		203 DPI
Printing method		Direct Thermal
Max.print speed		Max. 70mm (2.7") / s
Max.print width		72 mm (2.8")
Max.print length		1778 mm (70")
Media		
Media type		Continuous, gap, black mark
Media width		20 mm ~ 76 mm
Media thickness		0.06 mm ~0.254 mm
Label roll diameter		50mm
Performance Features		
Processor		32-bit CPU
Memory		8MB Flash Memory/ 8MB SDRAM
Interface		Standard version: USB+Bluetooth Optional:USB+WIFI
Screen		OLED (1.3") Resolution:128*64 pix
Sensors		①Gap sensor ②Cover opening sensor ③Black mark sensor
Fonts/Graphics/Symbologies		
Internal fonts		8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.
1D bar code		Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on,MSI, PLESSEY, POSTNET, China POST
2D bar code		PDF-417, Maxicode, DataMatrix, QR code,Aztec
Rotation		0°、 90°、 180°、 270°
Emulaion		TSPL、 EPL、 ZPL、 DPL、 CPCL、 ESC/POS
Physical Features		
Dimensions		124×108×61mm (D×W×H)
Weight		357 g
Reliability		
Printer head life		30Km
Software		
Operation system		Windows / Android / iOS
SDK		Windows / Android / iOS
Power supply		
USB		5V/1A
Battery		2500mAh
Environmental Conditions		
Operation environment		5 ~ 40°C (41~104°F) , Humidity: 25 ~ 85% no condensing
Storage environment		-40 ~ 60°C (-40~140°F) , Humidity: 10 ~ 90% no condensing

