



Retail



Hospitality



Ticketing



Kiosk

Confidence in Point-Of-Sale



Thermal POS Printer
VRP-POS88VI

VRP-POS88VI

POS

Features

- Automatic memory printing.
- Paper cover and cutter error being detected.
- Printing speed setting support.
- Anti-electromagnetic interference level 3.



Specifications

Printing Method	Thermal Line
Resolution	8dots/mm, 576dots/line
Effective Printing Width	72mm
Printing Speed	220mm/s
Character Set	ASCII, Codepage
Self-defined Character	YES
Print Font	Font A: 12 x24
Paper End Sensor	YES
Overheating Protection	YES
Power Supply (Adapter)	DC 24V, 2A
TPH	100KM
Auto Cutter	5,000,000 cuts
Paper Width	79.5± 0.5mm
Paper Thickness	0.06 to 0.08mm
Auto Cutter	Partial Cut
Operating Temp/Humidity	0-50°C/10%-80%
Storage Temp/Humidity	-20-60°C / 10%-90%
Dimension (LxWxH)	212x150x136mm
Graphic Interface	Support bitmap downloading RS-232/Parallel/USB/Ethernet/Wifi

*Specifications may change without prior notice.

		Saudi Arabia
	Jordan	+966 5969 42 631
Canada	+962 79 515 0428	+966 5940 42 440
+1 431 777 7777	+962 6 4 61 67 64	+966 11 4190874

Vtech@vtech-sys.com
www.vtech-sys.com